

## Fujitsu FUTRO S900 1.2 GHz G-T44R Windows Embedded Standard 7 1.3 kg Black

Brand : Fujitsu Product family: FUTRO Product code: LKN:S0900P0006FR

**Product name:** FUTRO S900

AMD G-Serie G-T44R (1.2 GHz, 512 KB L2 Cache), AMD A55E, 2GB DDR3 1066MHz, 4GB mSATA, AMD Radeon HD 6250, Gigabit Ethernet, Windows Embedded Standard 7, Black

Fujitsu FUTRO S900 1.2 GHz G-T44R Windows Embedded Standard 7 1.3 kg Black:

The individually configurable Fujitsu FUTRO S900 thin client has all the flexibility you need to optimize secure server-based computing and desktop virtualization. This simple, reliable yet powerful front-end device is easy to integrate and manage. It also offers expansion slots and unique connectivity options to maximize user convenience. Plus, its long lifecycle helps you minimize TCO.

## **Maximum Savings**

Thanks to cost-effective systems and automated roll-out your initial costs are kept on a low level. Subsequently you can achieve a TCO reduction of up to 80% thanks to low energy consumption and trouble-free computing.

## **Easy Manageability**

Manageability is facilitated thanks to central administration in the datacenter. As only low net load is required the performance of the solution is maintained.





Processor		Ports & interfaces	
Processor frequency * Processor model Processor family Processor cores L2 cache	1.2 GHz G-T44R AMD G 1 0.5 MB	DC-in jack DisplayPorts quantity DVI-I ports quantity Serial ports quantity Serial interface type	1 1 2 RS-232
Memory		Line-out PS/2 ports quantity	2
Internal memory * Internal memory type	2 GB DDR3-SDRAM	<b>Design</b>	2
Memory clock speed Memory slots Memory layout (slots x size)	1066 MHz 1x SO-DIMM 1 x 2 GB	Product colour * Cable lock slot Cable lock slot type	Black ✓ Kensington
Storage		Display	
Total storage capacity *	4 GB	Display included *	×
Storage media *	Flash	Software	
Graphics		Operating system installed *	Windows Embedded Standard 7
On-board graphics adapter model	AMD Radeon HD 6250	Power	
Maximum graphics adapter memory Maximum resolution	1920 x 1200 pixels	AC input voltage AC input frequency	100-240 V 50 - 60 Hz
Video		Operational conditions	
On-board graphics adapter	✓	Operating temperature (T-T)	10 - 35 °C
Network		Operating relative humidity (H-H)	5 - 85%
Wi-Fi *	X	Certificates	
Ethernet LAN *  Cabling technology 10	<b>√</b> 10/100/1000Base-T(X)	Certification	WEEE

Ports & interfaces		Sustainability	
VGA (D-Sub) ports quantity	N (RJ-45) ports * 1	Sustainability certificates	Rohs, Epeat Silver, Energy Stap
Ethernet LAN (RJ-45) ports * 1  USB 2.0 ports quantity * 8  Microphone in   Headphone outputs     1		Weight & dimensions	
	<b>√</b>	Width Depth	97 mm 191 mm
	1	Height	266 mm
		Weight	1.3 kg
		Other features	
		Graphics adapter family	AMD

